

Panasonic 65" TH-PF11 Plasma Display Specifications



FULL SPECIFICATIONS

DISPLAY

Display Format	1080p (FullHD)
Aspect Ratio	16:9
Contrast Ratio	30,000:1 (400:1)
Resolution	1920 x 1080
Pixel Pitch	0.747 x 0.747mm
Brightness	1200 cd/m ²
Analogue Video Input Signals	NTSC, PAL, SECAM, PAL60
HD Video Signal Compatibility	VGA, SVGA, XGA, WXGA, SXGA, UXGA (UXGA: Uncompressed)

INPUT TERMINALS

PC	Mini D-sub 15 pin x1
Video	1080/24p, 1080/60i, 480/60p, 720/60p, 1080/50i, 720/50p, 576/50p, 1080/50p, 1080/60p, 1080/30p, 480/60i
Audio	M3 jack x1
External Control	D-sub 9-pin x1 (Male) RS-232C compatible
Sound Output	8 ohms, 20 W [10W + 10W] (10% THD)

GENERAL

Power Supply	AC 230V (50/60 Hz)
Operation Distance	Approx 7m in front of plasma display
Power Consumption	710 Watt
Dimensions	Width: 1550mm Height: 930mm Depth: 99mm
Weight	68.0kg
Operating Temperature	Operating Temperature 0 to 40 °C Humidity 20 to 80 % (Non Condensation)
Storage Temperature	Operating Temperature -20 °C to 60 °C Humidity 20 to 90 % (Non Condensation)

Please note: All specifications are provided in good faith and believed to be up-to-date and accurate, but Revelation cannot accept liability for the use of information provided on this site. Revelation and its supplier manufacturers reserve the right to modify specifications without notice, but all details can of course be confirmed when arranging rental of any equipment from Revelation.

Plasma Screen Line Illustration Drawing

